

Specification Sheet

PEGDA Start PhotoInk™

Product description	Volumetric's PEGDA Start PhotoInk is a biocompatible and non-biodegradable bioink developed for the light based bioprinter Lumen X™. Ideal for bioprinting rigid microfluidic devices and tissue lattice structures with features $\geq 300 \mu\text{m}$. For a detailed instruction, follow the <i>Usage Protocol PEGDA Start PhotoInk</i> .
Composition	Composed of low (<2000 Da) PEGDA molecular weights.
Intended use	Biocompatible material for light based bioprinting, Research Grade . For research use ONLY. Not intended for <i>in vitro</i> diagnostics and <i>in vivo</i> uses. Not intended for administration in humans or animals.
Product number	D16110022060
Shelf life	Minimum 6 months, recommended use by date stated on vials.
Storage and handling	Store at 4 °C. Protect from light.
Shipping	Styrofoam box with ice packs.
Safety	Handle in accordance with good hygiene and laboratory safety practices. Read <i>Safety Data Sheet (SDS) PEGDA Start PhotoInk</i> for more information.
Related documents	Usage Protocol and Safety Data Sheet can be downloaded from our website at https://www.cellink.com/product/lumen-x-pegda-start-photoink-10ml/ . Scan the QR code below to reach it.

PhotoInk is a registered trademark of Volumetric. Lumen X is a registered trademark of CELLINK. All rights reserved.



Property	Specification	Method
<i>Form</i>	Liquid at ~22 °C	Visual inspection.
<i>Color</i>	Transparent, yellow	Visual inspection.
<i>Microbiological purity</i>	Sterile filtered	Single sterile filtered through 0.22 µm.
<i>Storage Modulus at End of Exposure</i>	50 ± 10 kPa	Photorheology, 100 µm gap, 90 s exposure at 20 mW/cm ²
<i>Exposure time</i>	1.75 ± 1 s	Printing at 50 µm thickness, 20 mW/cm ²
<i>Exposure time</i>	3 ± 1 s	Printing at 100 µm thickness, 20 mW/cm ²